

A Performance Evaluation of Modified Weighted Pathloss Scenario Based on the Cluster Based-PLE for an Indoor Positioning of Wireless Sensor Network

Cindha Riri Pratiwi^{1,*}, Prima Kristalina², Amang Sudarsono²

¹Graduate School of Electrical Engineering, Politeknik Elektronika Negeri Surabaya, Institute of Surabaya, Indonesia

²Department of Electrical Engineering, Politeknik Elektronika Negeri Surabaya, Institute of Surabaya, Indonesia

Received 31 March 2017; received in revised form 04 September 2017; accepted 09 October 2017

Abstract

The indoor positioning system is one of the popular topics in the current study; it is mainly due to the inability of the Global Positioning System (GPS) applied inside a building. LANDMARC (Location Identification based on Dynamic Active RFID Calibration) and Enhanced LANDMARC Scenario use calibration RSSI values and weighted process to obtain accuracy of position estimation. Meanwhile, WPL (Weighted Pathloss) method improves the positioning accuracy of the two previous methods (LANDMARC and Enhanced LANDMARC) by observing the Path Loss Exponent (PLE) value in an indoor environment, followed by using the value to estimate the object position. We propose a Modified WPL uses Cluster Based Pathloss Exponent (PLE) method by combining the functions of the existing calibration in LANDMARC Scenario with the Cluster Based PLE value. The test bed was conducted in an indoor area on the 3rd floor of the PENS Postgraduate Building. The nodes were connected to each other using X-Bee Pro S2 module. RSSI (Received Signal Strength Indicator) value was used to estimate the distance between transmitter and receiver nodes. The result of the MSE estimation position using the proposed method was 3.80 meters, whereas WPL method was 5.78 meters. Overall, the proposed Modified WPL with Cluster Based PLE method showed that it had the capability to enhance the accuracy of localization; 34% better than the standard WPL method.

Keywords: indoor positioning system, LANDMARC, WPL, cluster based PLE

References

- [1] I. T. Haque and C. Assi, "Profiling-based indoor localization schemes," *IEEE System Journal*, vol. 9, no. 1, pp. 76-85, 2015.
- [2] Z. Hengjun and Q. Hanbiao, "Research on the mine personnel localization algorithm based on the background of weak signal," *International Journal of Smart Home*, vol. 10, no. 7, pp. 47-56, 2016.
- [3] Z. De and L. G. Yan, "Positioning system of underground coal mines based on zigbee technology," *TELKOMNIKA Indonesian Journal of Electrical Engineering and Computer Science*, vol. 12, no. 5, pp. 3962-3968, 2014.
- [4] W. Yan, S. Xinxin, and J. Wei, "The mobile nodes location technology in wireless sensor network," *Chinese Journal of Sensor and Actuators*, vol. 24, no. 9, 2011.
- [5] B. Zhou, Q. Chen, and P. Xiao, "The error propagation analysis of the received signal strength based simultaneous localization and tracking in WSN," *IEEE Transaction on Information Theory*, vol. 63, pp. 3943-4007, 2017.
- [6] A. A. Momtaz, F. Behnia, R. Amini, and F. Marvash, "NLOS Identification in range based scene localization: Statistical Approach," *IEEE Sensor Journal*, vol. 18, pp. 3745-3751, 2017.
- [7] M. Singh and P. M. Khilar, "Mobile beacon based range free localization method for Wireless Sensor Networks," *Journal of Mobile Communication, Computation and Information*, vol. 23, pp. 1285-1300, 2017.

* Corresponding author. E-mail address: akucindha@gmail.com

- [8] K. Z. Lu, X. H. Xiang, D. Zhang, R. Mao, and Y. H. Feng, "Localization algorithm based on maximum a posteriori in wireless sensor networks," *International Journal of Distributed Sensor Networks*, vol. 2, no. 3, pp.198-214, 2012.
- [9] S. Tomic, M. Beko, R. Dinis, and P. Montezena, "Distributed algorithm for target localization in wireless sensor network using RSS and AOA measurement," *Elsavier Journal: Pervasive and Mobile Computing*, vol. 37, pp. 63-77, 2017.
- [10] M. Salamah and E. Doukhitch, "An efficient algorithm for mobile objects localization," *International Journal of Communication Systems*, vol. 21, no. 3, pp. 301-310, 2008.
- [11] A. Znaid, I. Idris, A. Wahab, L.K. Qabajeh, and O.A. Mahdi, "Sequential monte carlo localization method in mobile wireless sensor networks: a review," *Hindawi Journal of Sensors*, vol. 1, 2017.
- [12] N. U. Scholastica, "Path loss prediction model of a wireless sensor network in an indoor environment," *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering*, vol. 4, pp. 11665-11673, 2012.
- [13] R. D. Ainul, P. Kristalina, and A. Sudarsono, "A. modified iterative extended kalman filter for mobile cooperative tracking system," *International Journal of Advanced Science, Engineering and Information Technology*, vol. 21, no. 3, pp. 301-310, 2016.
- [14] F. Caballero, L. Merino, P. Gil, I. Maza, and A. Ollero, "A partial filter method for wireless sensor network localization with an aerial robot beacon," *Proc. 2008 IEEE International Conference on Robotics and Automation*, 2014, pp. 596-601.
- [15] X. Chen and S. Zou, "Improve wi-fi indoor positioning based on Partial Swarm Optimization," *IEEE Sensors Journal*, vol. 17, no. 21, 2017.
- [16] C. R. Pratiwi, P. Kristalina, and A. Sudarsono, "Cluster based Path Loss Exponent model for indoor estimation distance in wireless sensor network," *Proc. The 5th International Conference on Knowledge Creation and Intelligent Computing (KCIC), IEEE Xplore*, 2016, pp. 89-102.
- [17] Z. Yang, Y. Liu, and X. Li, "Beyond trilateration: on the localizability of wireless Ad Hoc networks," *IEEE /ACM Transactions on Networking*, vol. 18, no. 6, pp. 1806-1814, 2013.
- [18] P. Kristalina, A. Sudarsono, M. Syafrudin, and B.K. Putra, "SCLoc: secure localization platform for Indoor wireless sensor network," *Proc. 2016 International Electronics Symposium*, 2016, pp. 420-425.
- [19] L. M. Ni, Y. Liu, Y.C. Lau, and A.P. Patil, "LANDMARC: indoor localization sensing using RFID," *Wireless Network 10*, Kluwer Academic Publishers, 2004.
- [20] X. Jiang, Y. Liu, and X. Wang, "An enhanced approach of indoor location sensing using active RFID," *Wase International Conference of Information Engineering*, pp. 169-172, 2009.
- [21] H. Zou, L. Xie, Q. S. Jia, and H. Wang, "Platform and algorithm development for a RFID-based indoor positioning System," *Journal of Unmanned Systems*, vol. 2, no. 3, pp. 279-291, 2014.
- [22] B.R. Jadhavar and T.R. Sontakke, "2.4 GHz propagation prediction models for indoor wireless communications within building," *International Journal Science Computer Engineering*, vol. 2, no. 3, pp. 108-113, 2012.